Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Currently Amended) Windshield wiper device (10)-for a meter-vehicle, comprising a wiper bearing (16), a wiper shaft (22) positioned in a molded tube (18) of the wiper bearing (16) on which a wiper lever can be fastened, and a fastening element (20), which is embodied to be a one-part piece with the wiper bearing (16) and is used to fasten the windshield wiper device (10) to the motor vehicle, and at least one predetermined breaking point (32) such that the wiper bearing (16) is able to dip into the interior of the motor vehicle in case a defined, essentially axial force acts on the wiper shaft (22), characterized in that at least one predetermined breaking point (32) is embodied as a hole.
- (Original) Windshield wiper device (10) according to Claim 1, characterized in that the fastening element (20) is embodied as a plate-like projection and is embodied as a onepart piece with the molded tube (18).
- (Previously Presented) Windshield wiper device (10) according to Claim 1, characterized in that at least one hole has a circular or oval cross section.
- (Previously Presented) Windshield wiper device (10) according to Claim 1, characterized in that at least one hole has a rectangular cross section.
- (Previously Presented) Windshield wiper device (10) according to Claim 1, characterized in that at least one hole runs, with respect to its longitudinal axis, in the plane of the fastening element (20).

- (Previously Presented) Windshield wiper device (10) according to Claim 1, characterized in that at least one hole runs, with respect to its longitudinal axis, perpendicular to the plane of the fastening element (20).
- (Previously Presented) Windshield wiper device (10) according to Claim 1, characterized in that the wiper bearing (16) is embodied at least partially of plastic.
- (Currently Amended) Windshield wiper device (10) according to Claim 1, characterized in that the wiper bearing (16) is embodied at least partially of diecast, in particular zine or aluminum diecast.
- (Previously Presented) Windshield wiper device (10) according to Claim 1, characterized
 in that the predetermined breaking point (32) is arranged between the fastening point (34)
 of the fastening section (20) and the molded tube (18).
- (Previously Presented) Windshield wiper device (10) according to Claim 2, characterized in that at least one hole has a circular or oval cross section.
- (Previously Presented) Windshield wiper device (10) according to Claim 10, characterized in that at least one hole has a rectangular cross section.
- (Previously Presented) Windshield wiper device (10) according to Claim 11, characterized in that at least one hole runs, with respect to its longitudinal axis, in the plane of the fastening element (20).
- (Previously Presented) Windshield wiper device (10) to Claim 12, characterized in that
 at least one hole runs, with respect to its longitudinal axis, perpendicular to the plane of
 the fastening element (20).
- (Previously Presented) Windshield wiper device (10) according to Claim 13, characterized in that the wiper bearing (16) is embodied at least partially of plastic.

- (Currently Amended) Windshield wiper device (10) according to Claim 14, characterized in that the wiper bearing (16) is embodied at least partially of discast, in particular zine or aluminum diseast.
- 16. (Previously Presented) Windshield wiper device (10) according to Claim 15, characterized in that the predetermined breaking point (32) is arranged between the fastening point (34) of the fastening section (20) and the molded tube (18).